




1날 PMMA/PEEK/WAX 가공용 리브 볼 엔드밀 1 Flutes Rib Ball End Mills for PMMA & PEEK & WAX

호환 장비 (Competible Machine)
250i, 450i, 540i, DMG



1
WC 미립자
PMMA
PEEK
WAX
R ±0.01
D +0-0.01
30° Helix Angle

0.3 ~ 1.25R Ø0.6 ~ Ø2.5

- 플라스틱 (PMMA), PEEK, WAX, ABS 등 비철, 비금속 가공
- Endmills for PMMA, PEEK, WAX, A.B.S, non-ferrous and non-metallic materials.



단위 : mm

Order Number	날경 Diameter R × D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크소경 Shank Dia d1	샙크 Shank Dia d
1IME 006 070 S03	0.3R X 0.6	2	7	48	1.6	3
1IME 006 070 S06	0.3R X 0.6	2	7	53	4.2	6
1IME 0065 120 S03	0.325R X 0.65	2	12	48	1.6	3
1IME 0065 120 S06	0.325R X 0.65	2	12	53	4.2	6
1IME 010 160 S03	0.5R X 1	2	16	48	1.6	3
1IME 010 160 S06	0.5R X 1	2	16	53	4.2	6
1IME 020 200 S03	1R X 2	8	20	48	1.6	3
1IME 020 200 S06	1R X 2	8	20	53	4.2	6
1IME 025 200 S03	1.25R X 2.5	9	20	48	1.6	3
1IME 025 200 S06	1.25R X 2.5	9	20	53	4.2	6



2&3날 지르코니아 가공용 다이아몬드 코팅 볼 엔드밀 2&3 Flutes Diamond Coated Ball End Mills for Zirconia

호환 장비 (Competible Machine)
250i



2
3
WC 미립자
ZrO₂
NANO DIA. Coating
R ±0.01
D +0-0.01
30° Helix Angle

0.3 ~ 1.25R Ø0.6 ~ Ø2.5

- 지르코니아 (ZrO₂), 얼티메이트 (ULTIMATE) 등 비철 비금속 가공
- Endmills for Zirconia, Ultimate, non-ferrous and non-metallic materials.


단위 : mm

Order Number	날경 Diameter R × D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크소경 Shank Dia d1	샙크 Shank Dia d
2IME 006 070 S03	0.3R X 0.6	2	7	48	1.6	3
2IME 0065 120 S03	0.325R X 0.65	2	12	48	1.6	3
2IME 010 160 S03	3IME 010 160 S03	0.5R X 1	2	16	1.6	3
2IME 020 200 S03	3IME 020 200 S03	1R X 2	8	20	1.6	3
2IME 025 200 S03	3IME 025 200 S03	1.25R X 2.5	9	20	1.6	3



2&3날 지르코니아 가공용 다이아몬드 코팅 볼 엔드밀 2&3 Flutes Diamond Coated Ball End Mills for Zirconia

호환 장비 (Competible Machine)
450i, 540i, DMG



2
3
WC 미립자
ZrO₂
NANO DIA. Coating
R ±0.01
D +0-0.01
30° Helix Angle

0.3 ~ 1.25R Ø0.6 ~ Ø2.5

- 지르코니아 (ZrO₂), 얼티메이트 (ULTIMATE) 등 비철 비금속 가공
- Endmills for Zirconia, Ultimate, non-ferrous and non-metallic materials.

단위 : mm

Order Number	날경 Diameter R × D	날장 Length of cut L1	유효장 Effective Length L2	전장 Overall Length L	샙크소경 Shank Dia d1	샙크 Shank Dia d
2IME 006 070 S06	0.3R X 0.6	2	7	53	4.2	6
2IME 0065 120 S06	0.325R X 0.65	2	12	53	4.2	6
2IME 010 160 S06	3IME 010 160 S06	0.5R X 1	2	53	4.2	6
2IME 020 200 S06	3IME 020 200 S06	1R X 2	8	53	4.2	6
2IME 025 200 S06	3IME 025 200 S06	1.25R X 2.5	9	53	4.2	6

